

David-Link Biometric Safe



BIO-SEC-H1 Biometric Safe is ideal for securing personal valuables such as jewelry, diamonds, cash or guns in home, dormitory, hospital, hotel, school, cash room, boat, RV, or office with a simple touch. BIO-SEC-H1 is made from solid steel for added security, has 4 chrome bolts of 1/2" of an inch diameter mounting from bottom and back, and has a manual override key and external battery power pack.

External size W=16.5" L=15" H=8"

Internal size W=16" L=11" H = 7 1/2"

David-Link Biometric Safe

PRODUCT SPECIFICATIONS

Technical Specs Sheet (BioSec-H1)		
General Specs	Fingerprint Capacity	29
	Number of Override Key Included	2
	Identical Methods	FP, Key
	OperateVoltage	4~6.5V
Power Supply	Power Supply/ Power Source	4 x AA batteries
	Battery Life	At least 3,000 times
	Battery Backup	Yes
Fingerprint Reader	Resolution	500 dpi
	Reader Type	Optical sensor
	Working Temperature	from -13°F to 167°F
	Humidity Range	10%~80%
	Scanning Window Size	16*14mm
	FRR/FAR	< 1% / < 0.001%
Display	Display Type	LED
	Content on the Display	Power Mode, OK/NO
	Working Temperature	-10°C ~60°C
Parameters	External Dimension	W=16.5" L=15" H=8"
	Internal Dimension	W=16" L=11" H = 7 1/2"
	Thickness - Safe Body	0.5"
	Thickness - Safe Boor	2"
	Weight	28.6 lbs

Please call us for more detail and pricing

Nodaccess Solutions Inc
 26, St-Louis, Lemoyne, QC, J4R 2L4
 450-656-4837 / 877-711-4837
 info@nodaccess.com

