

## bioCLASS™ RKLB57, RWKLB575 and BIO500

Smart Card Reader/Field Enroller or Reader/Writer with Biometric Verification

• 6180, 6181, 6188, 6190

- ▶ **Increased Security** - Multi-factor authentication with smart card reader, keypad and fingerprint verification module
- ▶ **Reader and Field Enroller** - One unit (field enroller) provides access control verification and fingerprint template enrollment
- ▶ **Added Privacy** - Fingerprint templates are stored on the iCLASS® smart card to alleviate privacy and database management concerns
- ▶ **Compatibility** - Works with the broadest range of open standard contactless smart card products, available from over 40,000 resellers worldwide



### ACCESS interoperability.

Using 13.56 MHz contactless smart card technology, the bioCLASS™ RKLB57 and RWKLB575 family of readers provides users with new options for supporting multi-factor authentication of identity. Combining contactless card presentation with a fingerprint biometric, the bioCLASS reader can also be used with personal identification numbers (PIN).

Featuring multi-factor authentication, HID's bioCLASS readers offer the highest level of security. Storing the fingerprint template only on the smart card, users benefit from the increased security, faster throughput, easier system management, lower costs for the biometric reader and reduced concerns over individual privacy. Choose from three levels of security, including card/biometric fingerprint, card/PIN and card/fingerprint/PIN.\*

The bioCLASS RKLB57 is a read-only, contactless smart card reader with a keypad and biometric sensor that provides access control verification and fingerprint enrollment all in one reader.

- ▶ Field Enroller (6180BxR) can be configured as a dual-purpose reader/enroller, single-purpose enroller-only or reader-only
- ▶ Field Enroller (6180BxR) provides additional field configuration options allowing for selection of language (choose from 9 languages), administration rights (store rights on card or in reader) and template storage location (small templates fit anywhere on iCLASS® cards)
- ▶ Field Enroller comes with multilingual quick start guide and English instructional CD.
- ▶ Site unique keys protect card access control data (Elite) or biometric templates (Bio-Elite).

The bioCLASS RWKLB575 is a contactless smart card reader/writer with keypad and biometric sensor that provides access control verification, in addition to host-controlled read/write to iCLASS smart cards.

\* Security level configuration is not dynamic. Field or factory configurable using configuration card.

**Security** 64-bit authentication keys are extremely secure. Readers and cards require matching keys to function. All RF data transmission between the card and keypad reader is encrypted, using a secure algorithm. The key management system reduces the risk of compromised or duplicated cards.

**Graphical Display** The backlit graphical LCD display offers a 60 x 18 mm viewing area, 120 x 32 resolution. It is factory preset to provide written instructions to the user. Fully customizable, the display also describes the function of the user function keys. Multilingual version available in Field Enroller (6180BxR) unit.

**Keypad** Offers 12 discrete switches with metal keycaps. Raised tactile mark on the fifth key for visually impaired users. Configurable audio feedback. Backlit numbers in bezel overlay, above each key. Lighting is configurable: Always On, Triggered by Card Read, or Triggered by Key Press.

**Indoor Design** Rugged, weatherized polycarbonate enclosure provides reliable performance and resistance to vandalism. (Please note that these products are not suitable for outdoor use.)

**Enrollment** Use one of two methods for fingerprint template (and PIN enrollment if desired) onto iCLASS® smart cards. (1) Field Enroller (6180BxR) allows for dynamic configuration of reader type (reader/enroller, enroller-only or reader-only). Enroller-enabled reader types allows for enrollment of fingerprint templates (and PINs) onto iCLASS smart cards. (2) CP575A iCLASS Card Programmer is PC software that enables field programming of access card numbers, plus enrollment of fingerprint templates and PINs onto iCLASS smart cards.

<b>RKLB57 / RWKLB575</b>	
<b>Model Numbers</b>	<b>Field Enroller (Reader/Enroller)***</b> 6180BxR (Wiegand)
	<b>Reader ****</b> 6180BxT (Wiegand) 6188BxT (Clock-and-Data)
	<b>Reader / Writer *****</b> 6181BxT (Wiegand and RS232) 6181Bx4 (Wiegand and Full-Duplex RS485) 6181BxU (Wiegand and USB) 6181BxB (Wiegand and UART)
<b>Read Range</b>	iCLASS Card: Up to 4" (10.2 cm) iCLASS Key/Tag: Up to 1.25" (3.2 cm)
<b>Mounting</b>	Mounting plate attaches to US/EU/ Asian back box, 52-60 mm screw hole spacing (vertical or horizontal). LCD/Keypad reader housing latches onto mounting plate; fingerprint module secured to reader with a screw.
<b>Dimensions</b>	8.43" x 4.17" x 2.28" (21.4 x 10.6 x 5.8 cm)
<b>Weight</b>	13.5 oz. (382 g.)
<b>Power Supply</b>	9-12 VDC, Linear supply recommended
<b>* Current Requirements</b>	245 mA AVG, 299 mA PEAK
<b>Operating Temperature</b>	32° F to 113° F (0° C to 45° C)
<b>Operating Humidity</b>	5% to 95% relative humidity non-condensing
<b>Environmental</b>	Indoor Only
<b>Protection Class</b>	none
<b>Transmit Frequency</b>	13.56 MHz
<b>Cable Distance</b>	Wiegand/Clock-and-Data Interface: 500 ft (150 m) (22AWG), RS232: 50 ft (15 m), RS485: 4000 ft (1220 m), USB: 16 ft (4 m), UART: 1 ft (0.30 m)
<b>Card Compatibility</b>	iCLASS I5693 & I4443B - read-only on 16k bit (2k Byte), 32k bit (4k Byte); HID Application iCLASS I5693 & I4443B - read/write (RWKLB575 only) on 16k bit (2k Byte), 32k bit (4k Byte); Application Space
<b>Language Support**</b>	<b>Field Enroller</b> - English, International Spanish, Brazilian Portugese, German, Italian, French, Russian, Chinese (Mandarin), Korean, Japanese <b>Reader</b> - English, International Spanish, Brazilian Portugese, German, French, Chinese (Mandarin)
<b>Certifications</b>	UL294/cUL (US), FCC Certification (US), IC (Canada), CE (EU), C-tick (Australia, New Zealand), SRRC (China), MIC (Korea), NCC (Taiwan), MIC (Japan), iDA (Singapore), RoHS
<b>Housing Material</b>	UL94 Polycarbonate
<b>Fingerprint sensor type</b>	Optical
<b>Resolution</b>	500 dpi, 256-bit gray scale, 18 x 22 mm sensor area
<b>Timing</b>	Card read < 0.5 sec Fingerprint capture < 2 sec, typical 1 sec Verification of captured finger < 1 sec
<b>False Accept/Reject Rate</b>	FAR < 0.01%, FRR < 0.01%
<b>Warranty</b>	Warrantied against defects in materials and workmanship for one year. (See complete warranty policy for details.)

\*\* (RWKLB575 specific) Add 25 mA current for USB expansion modules and 20 mA for all others.

\*\*\* Language support includes LCD text and quick start document.

\*\*\*\* Field Enroller (Reader/Enroller) is field configurable into Reader/Enroller, Enroller-Only or Reader-Only reader types. Additionally, LCD language is field configurable.

\*\*\*\*\* Legacy reader part numbers support simpler installation (no setup required) and C&D support. For maximum flexibility, select the Field Enroller.

\*\*\*\*\* One serial hardware interface only supported by RWKLB575 with expansion module.

© 2009 HID Global. All rights reserved. HID, the HID logo, and iCLASS are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 06/2009

MKT-bioCLASS\_REVB\_DS-EN



**ACCESS experience.**

**hidglobal.com**

**Corporate North America**  
15370 Barranca Pkwy  
Irvine, CA 92618  
U.S.A.  
Tel: 1 800 237 7769  
Tel: +1 949 732 2000  
Fax: +1 949 732 2360

**Asia Pacific**  
19/F 625 King's Road  
North Point  
Island East  
Hong Kong  
Tel: +852 3160 9800  
Fax: +852 3160 4809

**Latin America**  
Circunvalacion Ote. #201 B  
Despacho 2  
Col. Jardines del Moral  
Leon 37160, Gto.  
Mexico  
Tel: +52 477 779 1492  
Fax: +52 477 779 1493

**Europe, Middle East & Africa**  
Haverhill Business Park  
Phoenix Road  
Haverhill, Suffolk  
CB9 7AE  
England  
Tel: +44 (0) 1440 714 850  
Fax: +44 (0) 1440 714 840